

ZT3000



Bobcat®

One Tough Animal.

**BUILT FOR THE
TOUGHEST
CUSTOMER:**

ME

BRING TOUGH TO TURF

DELIVERS A QUALITY CUT

You're doing this because you love it. Pride in a job well done. That's the ZT3000's sweet spot, no matter how many acres you maintain.



ZT3000

MODEL NUMBER	9993001	9993002	9993003
ENGINE			
Model	Kaw FT651V	Kaw FT691V	Kaw FT730V
Displacement		44.3 cu. in. (726 cc)	
Fuel Capacity		3.8 gal. (14.3 L)	
Air Filter		Dual Element	
ELECTRICAL			
Charging System		15 amp	
Clutch		125 lbf. (556 N)	
DECK			
Mower Deck	TufDeck™ Pro 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts		
Width	48.0 in. (1219 mm)	52.0 in. (1320 mm)	61.0 in. (1549 mm)
Adjustable Anti-Scalp Rollers	3	3	7
Cutting Height	1.5-4.8 in. (38-121 mm)		
Blade Tip Speed	17,365 fpm @ 3550 Engine rpm	18,142 fpm @ 3550 Engine rpm	18,809 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer		
FRAME			
Front & Rear	Welded, 7-gauge Steel; 1.5 x 2.5 in. Steel Tubing		
Machine Length	76.0 in. (1930 mm)		
Machine Weight	758 wet lb.	774 wet lb.	817 wet lb.
TRANSMISSION			
Type	HG ZT-3100 Hydrostatic Transaxles		
Pump Displacement	0.6 cu. in. (10 cc)		
Oil Capacity	1.0 gal. (4 qt)		
Forward Speed	0-8.0 mph (0-12.8 km/hr.)		
Reverse Speed (mph)	0-3.5 mph (0-5.6 km/hr.)		
WHEELS			
Drive Wheel Size	22 x 11.0-10		
Front Caster Wheel Size	13 x 6.5-6		
Caster Arm Attachment	Welded to Frame		
SEAT			
Description	High-Back, EVC and Spring Suspension Seat		
Fore-Aft Adjustment	Seat Slide Lever		

1000
HOURS

BUMPER TO BUMPER

WARRANTY



YOU ARE ONE TOUGH ANIMAL.®

Everything we put into Bobcat equipment is designed to make more of whatever you bring to the job. Whether it's strength, versatility, speed or agility, it's built around you.

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors. Where applicable, dimensions are in accordance with ISO standards. Specifications and design are subject to change without notice. Pictures of Bobcat units may show other than standard equipment. All dimensions are given for mini track loaders. All dimensions are shown in inches. Respective metric dimensions are enclosed by parentheses. Bobcat Company complies with the requirements of ISO 9001 as registered with BSI.

Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2020 Bobcat Company. All rights reserved.



B-1999 (08/20)

Bobcat Company
250 East Beaton Drive • West Fargo, ND 58078

Bobcat.com



Bobcat®

One Tough Animal.