

ZT6000



Bobcat®

One Tough Animal.

BUILT TO

WORK

BRING TOUGH TO TURF

VERSATILITY AND DEPENDABILITY DEFINED

The ZT6000 will satisfy the toughest customers and give your crew something to fight over.



ZT6000

| MODEL NUMBER | 9996010 | 9996011 |
|-------------------------------|---|------------------------------|
| ENGINE | | |
| Model | Kaw FX801V | |
| Displacement | 52.0 cu. in. (852 cc) | |
| Fuel Capacity | 15 gal. (56.7 L) | |
| Air Filter | Canister Air Filter | |
| ELECTRICAL | | |
| Charging System | 15 amp | |
| Clutch | 225 lbf. (1000 N) | |
| DECK | | |
| Mower Deck | AirFX™ Cutting System | |
| Leading Edge | Adjustable, Front Lip Standard | |
| Width | 52 in. (1320 mm) | 61 in. (1541 mm) |
| Adjustable Anti-Scalp Rollers | 6 | |
| Cutting Height | 1.0-5.5 in. (25-139 mm) | |
| Blade Tip Speed | 18,586 fpm @ 3550 Engine rpm | 18,500 fpm @ 3550 Engine rpm |
| Discharge Chute | Flexible Molded Polymer | |
| FRAME | | |
| Front & Rear | Welded, 0.25 in., 7-gauge Steel; 1.5 x 2.5 in. Steel Tubing | |
| Machine Length | 83.0 in. (2108 mm) | |
| Machine Weight | 1371 wet lb. | 1421 wet lb. |
| TRANSMISSION | | |
| Type | HG ZT-4400 Hydrostatic Transaxles | |
| Pump Displacement | 0.7 cu. in. (12 cc) | |
| Oil Capacity | 1.1 gal. (4.5 qt.) each | |
| Forward Speed | 0-12.0 mph (0-19.3 km/hr.) | |
| Reverse Speed (mph) | 0-4.0 mph (0-6.4 km/hr.) | |
| WHEELS | | |
| Drive Wheel Size | 24 x 10.5-12 | |
| Front Caster Wheel Size | 13 x 6.5-6 | |
| Caster Arm Attachment | Bolt-On | |
| SEAT | | |
| Description | High-Back, Full-Mechanical Suspension Seat | |
| Fore-Aft Adjustment | Seat Slide Lever | |

**2000
HOURS**

BUMPER TO BUMPER

WARRANTY



YOU ARE ONE TOUGH ANIMAL.®

Everything we put into Bobcat equipment is designed to make more of whatever you bring to the job. Whether it's strength, versatility, speed or agility, it's built around you.

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Bobcat equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors. Where applicable, dimensions are in accordance with ISO standards. Specifications and design are subject to change without notice. Pictures of Bobcat units may show other than standard equipment. All dimensions are given for mini track loaders. All dimensions are shown in inches. Respective metric dimensions are enclosed by parentheses. Bobcat Company complies with the requirements of ISO 9001 as registered with BSI.

Bobcat®, the Bobcat logo and the colors of the Bobcat machine are registered trademarks of Bobcat Company in the United States and various other countries. ©2020 Bobcat Company. All rights reserved.



Printed on 10% recycled paper

B-2001 (08/20)

Bobcat Company

250 East Beaton Drive • West Fargo, ND 58078

Bobcat.com



Bobcat®

One Tough Animal.